





4FRONT 2 - TB3 SEAT / LIFT / TILT / RECLINE

DEALERS DETAILS		DELIVERY DETAILS		
Dealers Name		Dealers Address		
Order Date				
Address				
	Postcode	Postcode		
Phone	Email	Quantum Specialist		
PO No	Order Ref	© Clients Weight (required for suspension settings)		

BASE MODEL

14 Colour Options Height Adjustable Removable Armrests Centre Mount Foot Platform **TB3 Seating** 14" Flat Free Drive Tyres 2" x 9" Flat Free Rear Castors

Standard = Standard Factory Feature FOC = Select Instead of Standard Factory Feature



SRS Suspension System **Smart Traction Control** Q-Logic 3e Control System 2 x 70 ah Batteries 6 Mph (9.65 Km/h) 4-Pole Motors Max User Weight: 21 st 6lbs. (136 kg)

DRIVE WHEELS

3" x 14" Flat Free Black Tyres. With matching colour wheel accents.	Standard
3" x 14" Pneumatic Black Tyres. With matching colour wheel accents.	FOC

COLOURS

Back in Black	Standard	
Green Machine	FOC	
Midnight Blue	FOC	
Electric Blue	FOC	
Blue Jean	FOC	
Deep Purple	FOC	
Red Corvette	FOC	

Pretty in Pink	FOC
Lemon Crush*	FOC
Night Train*	FOC
Evolution Orange*	FOC
Military Green*	FOC
Grey Street*	FOC
Raspberry Beret*	FOC

^{*} Extended lead-time.

Please download our free PQ-365 app to view colours and other product features in more detail.









SEAT PACKAGES - SEAT WIDTH SEAT PACKAGES - SEAT DEPTH 14"-16"W. 14"-16"D. 16"-20"W. 16"-20"D. 20"-22"W. 20"-22"D. Set width at: Set depth at:

STEALTH SEAT CUSHIONS

No Seat Cushion Required	FOC
Zen SP: Skin Protection, 4-way Stretch, Coolcore Cover. 160 Kg weight limit.	Standard
Simplicity G: General Use, Fluid Resistant Stealth-Tek Cover. 158.7 Kg weight limit.	FOC
TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. 158.7 Kg weight limit.	FOC

Please note that seat cushions may not be available in all width and depth combinations. Refer to our Stealth Cushion Order Forms for size availability.

SEAT POSITIONING

Powered Seat Lift & Tilt. 10" lift & 50° tilt. Up to 3.5 Mph drive speed while elevated. Uses 2 power options.				
Powered iLevel Lift & Tilt Seat to Floor Height. From seat pan.	17.75″	18.75"	19.75"	

BACKREST SPECIFICATIONS

TRU-Balance 3 Back Support System. *Include a metal active contour back support shell, TRU-Comfort 2 back cushion, and a set of wedge inserts. Select TB3 back*

Standard

TB3 BACK SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. Select size in Back Support Dimensions Standard

TB3 BACK SUPPORT POSTIONING

TRU-Balance 3 Powered Recline. 175° with sheer reduction. Uses 1 power option.

Standard

BACK SUPPORT DIMENSIONS

 $Compatible\ with\ TB3\ and\ Back\ Canes\ options\ above.\ Back\ Support\ can\ be\ +/-\ 4"\ of\ seat\ width\ with\ TB3\ Back\ Support\ System,\ but\ must\ be\ same\ as\ seat\ width\ with\ Back\ Canes\ Only\ System\ unless\ -2"\ or\ -4"\ Endo\ Mounts\ have\ been\ selected.$

Backrest Support Width Package		12"-14"W.	14"-16"W.	16"-20"W.
		18"-22"W.	20"-24"W.	
Back	12″W.	14″W.	16″W.	17″W.
Support Width.	18″W.	19″W.	20″W.	21″W.
	22″W.	24″W.		
Back – Support Height. From seat pan.	19"H.	20″H.	21″H.	22″H.
	23″H.	24″H.	25"H. Not available with 24"W back.	26"H. Not available with 24"W back.
	27"H. Not available with 24"W back.	28"H. Not available with 24"W back.	29"H. Not available with 24"W back.	

2-Post Flip-up Removab	le. Adjustment range 9" t	to 13″ from seat p	oan.			Standard
Paediatric Single Post Ho	eight Adjustable. <i>Adju</i> s	stment range 7.7	'5"- 9.75" from sec	at pan. 10″ pads only	:	FO
Single Post Drop-in Rem	novable. <i>Adjustment ran</i>	ge 11"-17" from :	seat pan.			FO
TB3 Flip-back. Adjustmen	t range 8″-16″ from seat p	oan. Includes late	ral in/out adjustr	nent.		FOO
Awas Cours a wt Da da	10" Standard	Star	ndard	10" Waterfall.		FOO
Arm Support Pads.	14" Standard	• • • • • • • • • • • • • • • • • • • •	FOC	14" Waterfall.		FOO
ENTRE MOUNTED L	EG SUPPORTS					
Manually Adjustable Ce	ntre Mount Foot Platfo	orm.				Standard
Paediatric Adj. Centre M	lount Foot Platform. 12	2″-14″ seat width	ns only.			FOO
Lower Leg Extensions. From seat pan.	8"-12". Paediatric centre mount only.	FOC	10″-16″.	Standard	13″-19″.	FOO
Footplates	10″W x 6″D Split	Footplates. <i>Pa</i>	ediatric centre m	ount only.	•	FOO
rootplates. –	10"W x 8"D Split	Footplates.	FOC	10"W x 11"D	Split Footplates.	Standard
Calf Support.	Individual Calf Pa	ads. <i>6"W x 6"H</i> .	• • • • • • • • • • • • • • • • • • • •		•	Standard
	Certain configurations ma	av result in reduce	d ground clearance	a helow footplates. Co	ntact Quantum Technica	l for information
Manual Elevating Swing				stment range 7" to 1 Min. seat width 15".	1″.	
	ı-Away Legrests. <i>Flip-u</i>	p footplates. Adj.	range 15" to 20".	Min. seat width 15".	1".	
Manual Elevating Swing	ı-Away Legrests. <i>Flip-u</i>	p footplates. Adj.	range 15" to 20".	Min. seat width 15".	1".	FOO
	y-Away Legrests. Flip-up	p footplates. Adj.	range 15" to 20".	Min. seat width 15".		
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions.	y-Away Legrests. Flip-up	JRABLE LI upports. Select I	range 15" to 20". EG SUPPO owers and footpl 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard		FOO FOO
60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan.	NTED CONFIGURE Swing-away Leg Su	JRABLE LI upports. Select I FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO FOO Standard
60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan.	NTED CONFIGURIES Swing-away Leg Sun 11"-13"	JRABLE LI upports. Select I FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO FOO Standard
60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan.	NTED CONFIGURE Swing-away Leg Sure 11"-13" Flip-up Extrudes	JRABLE LI upports. Select I FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO FOO Standard
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI	NTED CONFIGURE Swing-away Leg Surface Swing-away Leg Surface Swing-away Leg Surface Su	JRABLE LI upports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO FOO Standard
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI UniLink 8" Comfort Plus.	NTED CONFIGURE NTED CONFIGURE Suing-away Leg Sure 11"-13" Flip-up Extrude PORTS . HMO475-17M / CP08CCE	JRABLE LI Ipports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FO Standard FO Standard
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI UniLink 8" Comfort Plus. UniLink 10" Comfort Plus.	NTED CONFIGURE NTED CONFIGURE Suing-away Leg Sure 11"-13" Flip-up Extrude PORTS . HMO475-17M / CP08CCE	JRABLE LI Ipports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO Standard FOO Standard
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI UniLink 8" Comfort Plus. UniLink 10" Comfort Plus.	NTED CONFIGURE NTED CONFIGURE Suing-away Leg Sure 11"-13" Flip-up Extrude PORTS . HMO475-17M / CP08CCE	JRABLE LI Ipports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO Standard FOO Standard
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI UniLink 8" Comfort Plus. UniLink 10" Comfort Plus. UniLink 14" Comfort Plus.	NTED CONFIGURE NTED CONFIGURE PORTS HM0475-17M / CP10CO S. HM0475-17M / CP14CO S. HM0475-17M / CP14CO S. HM0475-17M / CP14CO	JRABLE LI Ipports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO Standard FOO Standard FOO
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI UniLink 8" Comfort Plus. UniLink 10" Comfort Plu UniLink 14" Comfort Plu ELVIC BELTS	NTED CONFIGURE NTED CONFIGURE IL Swing-away Leg Sure 11"-13" Flip-up Extrude PORTS . HMO475-17M / CP08CCI IS. HMO475-17M / CP14CCI IS. HMO475-17M / CP14CI IS. HMO475	JRABLE LI Ipports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO FOO Standard
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI UniLink 8" Comfort Plus. UniLink 10" Comfort Plu UniLink 14" Comfort Plu ELVIC BELTS Auto Buckle Lap Belt, Pu	NTED CONFIGURE Swing-away Leg Suran 11"-13" Flip-up Extruder PORTS . HMO475-17M / CP08CCE IS. HMO475-17M / CP14CCE IS. HMO475-17M / CP14CE IS. HMO47	JRABLE LI Ipports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl. 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO Standard FOO Standard FOO
ADIVIDUALLY MOU 60° to 90° Tool Adjustab Lower Leg Extensions. From seat pan. Footplate Type. TEALTH HEAD SUPI UniLink 8" Comfort Plus. UniLink 10" Comfort Plus. UniLink 14" Comfort Plus. Auto Buckle Lap Belt, Pu XPANDABLE CONT	NTED CONFIGURE Swing-away Leg Suran 11"-13" Flip-up Extruder PORTS . HMO475-17M / CP08CCE IS. HMO475-17M / CP14CCE IS. HMO475-17M / CP14CE IS. HMO47	JRABLE LI Ipports. Select II FOC d. 8.5"W x 6"D.	range 15" to 20". EG SUPPO owers and footpl 13.5"-16.5"	Min. seat width 15". RTS ates below. Minimun Standard	n seat width 15". 15.5"-19.5"	FOO FOO Standard FOO Standard

HAND CONTROL MOUNTS

	Fixed.	Standard				
	Swing-away. Swings in 8	& out with height, ten	sion and pivot adjustme	nt.		FOC
:	Mounting Position.	Left	FOC	Right	Standard	

SPEED PROGRAM & LIGHTS PACKAGE

6 Mph Program with Lights and indicators.	Standard
4 Mph Program with Lights and indicators.	FOC
LED Fender Lights. Includes single switch button mounted to side rail. Not road legal.	Standard
Omit LED Fender Lights.	FOC

NOTES & SPECIAL REQUESTS





32 Wedgwood Road, Bicester, Oxon, OX26 4UL Phone: 01869 324600 Fax: 01869 323070 Email: sales@quantumrehab.co.uk Web: www.quantumrehab.co.uk MOTABILITY ID 1000835 - 29/03/23 V1













