





MOTABILITY ID 714945

Q6 EDGE HD WITH TB3 SEATING

DEALERS DETAILS

Postcode
Email
Order Ref
F

DELIVERY DETAILS

Dealers Address

Quantum Specialist

Clients Weight

BASE MODEL

10 Colour Options

- Height Adjustable Removable Armrests
- Flip-up Centre Mount Foot Platform
- Angle Adjustable Back Support
- Spectrum Foam SPP Seat Cushion
- 14" Flat Free Drive Tyres
- 2" x 6" Flat Free Front Castors

Standard = Standard Factory Feature FOC = Select Instead of Standard Factory Feature

DRIVE WHEELS

3" x 14" Flat Free Black Tyres.	Standard
3" x 14" Pneumatic Black Tyres.	FOC

COLOURS

Back in Black	Standard
Night Train	FOC
Electric Blue	FOC
Midnight Blue	FOC
Deep Purple	FOC
Red Corvette	FOC

Pretty in Pink	FOC
Evolution Orange	FOC
Grey Street	FOC
Green Machine	FOC
	<

Please download our free PQ-365 app to view colours and other product features in more detail.





SEAT PACKAGES - SEAT WIDTH



SEAT PACKAGES - SEAT DEPTH

20"-25"D

Set depth at:

ATX Suspension System Q-Logic 3e Control System 2 x 70 ah Batteries 4 Mph (6 Km/h) Motors Max User Weight: 32 st 2lbs. (204 kg)

2" x 6" Flat Free Rear Castors

Postcode

STEALTH SEAT CUSHIONS

No Seat Cushion Required	FC
Spectrum Foam SPP: Skin Protection, Positioning, 4-way Stretch, Coolcore Cover, Urethane Liner. 226.7 Kg weight limit.	S
TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. 204 Kg weight limit.	F
Spectrum Gel SPP: Skin Protection, Positioning, 4-way Stretch, Coolcore Cover, Urethane Liner. 340 Kg weight limit.	F

SEAT POSITIONING

Static Seat.StandardStatic Seat to Floor Height. From seat pan.16.5"17.5"18.5"

Please note that seat cushions may not be available in all width and depth combinations.

Select one option above. Both options above include a metal active contour back support shell,

Refer to our Stealth Cushion Order Forms for size availability.

TRU-Comfort 2 back cushion, and a set of wedge inserts.

BACKREST SPECIFICATIONS

TRU-Balance 3 Back Support System. Select TB3 back options below. Ignore all 'Back Cane' options.	Standard
Back Canes Only System. Not available with TB3 flip-back arm supports. Move directly to 'Back Cane Only Support Options' if selected.	FOC

TB3 BACK SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. Standard

Select size in Back Support Dimensions

TB3 BACK SUPPORT POSTIONING

TRU-Balance 3 Static Back. Angle can be preset manually.	Standard
TRU-Balance 3 Flip-forward Back. Not available with TB3 flip-back arm supports.	FOC

BACK CANE ONLY SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. Select size in Back Support Dimensions						Standard
Back Cane Only	Support Positioni	ng.	Tool Angle Ac	ljustable. 85° to 120° in 5	° increments.	Standard
Back Cane	16″H.	17″H.	18″H.	19″H.	20″H.	
Height. — From seat pan.	21″H.	22″H.	23″H.	24″H.	25″H.	

BACK SUPPORT DIMENSIONS

Compatible with TB3 and Back Canes options above. Back Support can be +/- 4" of seat width with TB3 Back Support System, but must be same as seat width with Back Canes Only System unless -2" or -4" Endo Mounts have been selected.

Backrest Supp	ort Width Package.	16″-20″W.		20″-24″W.
Duckiest Supp	ort matri ackage.	14″-28″W.		28″-32″W.
Back	18″W.	19″W.	20″W.	21″W.
Support Width.	22″W.	24″W.	26″W.	28″W.
width.	30″W.	32″W.		
Back	16″H.	17″H.	18″H.	19″H.
Support	20″H.	21″H.	22″H.	23″H.
Height. From seat	24″H.	25″H.	26″H.	27″H.
pan.	28″H.			

Height Adjustable, Remo	ovable, Heavy Duty.		Standarc
HD Removable Height Package. <i>From seat pan.</i>	8″-12″.	FOC 10"-14".	Standard
TB3 Flip-back with Dowi	n Posts. Adjustment range 8"	-16″ from seat pan. Includes lateral in/out adjustmen	t. FOC
	10″ Standard		Standard
	10" Standard 14" Standard		Standarc FOC
Arm Support Pads.	14" Standard	nly. Minimum seat depth 16".	
Arm Support Pads.	14" Standard	nly. Minimum seat depth 16″.	FOO

CENTRE MOUNTED LEG SUPPORTS

Base Mounted Flip-up Foot Platform. <i>Mounted to chassis</i> .				
Manually Adjustable Ce	ntre Mount Foot Platform. Mounted to	o seat.		Standard
Lower Leg Extensions. From seat pan.	10″-16″.	Standard	13"-19".	FOC
Footplates.	10"W x 8"D Split Footplates.	FOC	10"W x 11"D Split Footplates.	Standard
Calf Support.	Individual Calf Pads. 6"W x 6"H.	Standard	Calf Panel. 18"W x 8"H.	FOC
	Individual Large Calf Pads. 8"W x 8"H tapering to 6"W.	£42		
	Certain configurations may result in reduce	d ground clearai	nce below footplates. Contact Quantum Technical	for information.

INDIVIDUALLY MOUNTED CONFIGURABLE LEG SUPPORTS

	70° Heavy Duty, Drop-in, Swing-away Leg Supports. <i>Select lowers and footplates below.</i>						
₽	Lower Leg Extensions. From seat pan.	8.5″-12″	FOC	13″-18″	Standard	16"-21"	FOC
70° H	Footplate Type.	Angle & Dept	h Adjustable. Se	lect size below.			Standard
	Footplate Size.	6″W x 8″D	Standard	6″W x 11″D	FOC	8″W x 11″D	FOC
	Heavy Duty, Manual Elevating, Swing-away Leg Supports.						
	Lower Leg Extensions.	11″-14″	FOC	14"-17"	Standard	12.5″-16.5″	FOC
	From seat pan.	15.5″-19.5″	FOC				
G HD	Footplate Type. —	Flip-up Extru	ded. 8.5″W x 6″D.			Standard	
ATIN		Angle & Depth Adjustable. Select size below.					FOC
ELEV	Footplate Size. —	6″W x 8″D					Standard
	Angle adj. only.	6″W x 11″D					FOC
		8″W x 11″D					FOC

STEALTH HEAD SUPPORTS

UniLink 8" Comfort Plus. HMO475-17M / CP08CCFPM.	FOC
UniLink 10" Comfort Plus. HMO475-17M / CP10CCFPM.	Standard
UniLink 14" Adjustable Comfort Plus. HMO475-17M/ ACP150M.	FOC

Pelvic Belts.	Auto Buckle Lap Belt, Push Button Release.	Standard
EXPANDABL	E CONTROLS	
Q-Logic 3e Controls. No power options.		Standarc
Control Method.	Hand Control. Select position in Hand Control Mounts below.	Standarc
	Attendant Control. Hand control mounted at rear.	FOC

Swing-away. Swings	FOC				
Mounting Position.	Left	FOC	Right	Standard	

SPEED PROGRAM & LIGHTS PACKAGE

4 Mph Program with Lights and indicators.

NOTES & SPECIAL REQUESTS



Quantum®

32 Wedgwood Road, Bicester, Oxon, OX26 4UL Phone: 01869 324600 Fax: 01869 323070 Email: sales@quantumrehab.co.uk Web: www.quantumrehab.co.uk **MOTABILITY ID 714945 - 11/08/23 V1**



V1: 14/06/2022

Standard