





MOTABILITY ID 1000793

R-TRAK WITH TB3 SEATING

DEALERS DETAILS		DELIVERY DETAILS	
Dealers Name		Dealers Address	
Order Date			
Address			
	Postcode	Postcode	
Phone	Email	Quantum Specialist	
PO No	Order Ref	① Clients Weight	

BASE MODEL

14 Colour Options
Height Adjustable Removable Armrests
Centre Mount Foot Platform
TB3 Seating
14" Flat Free Drive Tyres
2" x 9" Flat Free Front Castors

Standard = Standard Factory Feature FOC = Select Instead of Standard Factory Feature



ATX Suspension System
Q-Logic 3e Control System
2 x 70 ah Batteries
4 Mph (6 Km/h) Motors
Max User Weight:
21 st 6lbs. (136 kg)

DRIVE WHEELS

3" x 14" Flat Free Black Tyres. With matching colour wheel accents.	Standard
3" x 14" Pneumatic Black Tyres. With matching colour wheel accents.	FOC

COLOURS

Back in Black	Standard
Green Machine	FOC
Midnight Blue	FOC
Electric Blue	FOC
Blue Jean	FOC
Deep Purple	FOC
Red Corvette	FOC

Pretty in Pink	FOC
Lemon Crush*	FOC
Night Train*	FOC
Evolution Orange*	FOC
Military Green*	FOC
Grey Street*	FOC
Raspberry Beret*	FOC

* Extended lead-time.

Please download our free PQ-365 app to view colours and other product features in more detail.









42// 45///		10" 16"5		
12"-16"W.		12"-16"D.		
14"-16"W.		14"-16"D.		
16"-20"W.		16"-20"D.		
20"-22"W.		20"-22"D.		
Set width at:	•••••••••••••••••••••••••••••••••••••••	Set depth at:		•
No Seat Cushion Required				FO
Simplicity G: General Use, Fluid Resista	nt Stealth-Tek Cove	er. 158.7 Ka weiaht limit		Standard
Zen SP: Skin Protection, 4-way Stretch,				FOO
TRU-Comfort 2 SPP: Skin Protection, Po			weight limit	FOO
Please note that seat cushions may not be				
Static Seat to Floor Height From section				Standar
Static Seat to Floor Height. From seat pan.		15″	16"	17"
ACKREST SPECIFICATIONS	plact TP2 hask antions			
	ith Power recline or TB	below. Ignore all 'Back Cane' optio		Standard
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. Se Back Canes Only System. Not available w Move directly to 'Back Cane Only Support Opi Select one option above. Both options above	ith Power recline or TB tions' if selected.	below. Ignore all 'Back Cane' optio 13 flip-back arm supports.	ns.	Standard FOO
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. Se Back Canes Only System. Not available w Move directly to 'Back Cane Only Support Opi	ith Power recline or TB tions' if selected. ve include a metal active	below. Ignore all 'Back Cane' optio. 33 flip-back arm supports. e contour back support shell, TRU-Com	ns.	Standard FOO of wedge insert
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. See Back Canes Only System. Not available we Move directly to 'Back Cane Only Support Opens Select one option above. Both options above B3 BACK SUPPORT Active Contour Back Support with TRU-Select size in Back Support Dimensions B3 BACK SUPPORT POSTIONI	ith Power recline or TB tions' if selected. ve include a metal active -Comfort 2 Back Cu	below. Ignore all 'Back Cane' optio. 33 flip-back arm supports. e contour back support shell, TRU-Com	ns.	Standard FOO of wedge insert Standard
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. See Back Canes Only System. Not available we Move directly to 'Back Cane Only Support Options above. Both options above. Both options above. Back Support Select one option above. Both options above. Back Support Select size in Back Support Dimensions	ith Power recline or TB tions' if selected. ve include a metal active -Comfort 2 Back Cu	below. Ignore all 'Back Cane' option 33 flip-back arm supports. e contour back support shell, TRU-Com ushion and Wedge Inserts.	ns. Ifort 2 back cushion, and a set o	Standard FOO of wedge insert Standard Standard
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. See Back Canes Only System. Not available we Move directly to 'Back Cane Only Support Open Select one option above. Both options above B3 BACK SUPPORT Active Contour Back Support with TRU-Select size in Back Support Dimensions B3 BACK SUPPORT POSTIONI TRU-Balance 3 Static Back. Angle can be page.	ith Power recline or TB tions' if selected. ve include a metal active -Comfort 2 Back Cu	below. Ignore all 'Back Cane' option 33 flip-back arm supports. e contour back support shell, TRU-Com ushion and Wedge Inserts.	ns. Ifort 2 back cushion, and a set o	Standard FOO of wedge insert Standard Standard
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. See Back Canes Only System. Not available we Move directly to 'Back Cane Only Support Options above Select one option above. Both options above B3 BACK SUPPORT Active Contour Back Support with TRU-Select size in Back Support Dimensions B3 BACK SUPPORT POSTIONI TRU-Balance 3 Static Back. Angle can be particularly and the second services of the second second services of the second	ith Power recline or TB tions' if selected. ve include a metal active -Comfort 2 Back Cu NG preset manually. vailable with TB3 flip-b	below. Ignore all 'Back Cane' option 33 flip-back arm supports. e contour back support shell, TRU-Comushion and Wedge Inserts.	ns. Infort 2 back cushion, and a set of	Standard FOO
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. See Back Canes Only System. Not available we Move directly to 'Back Cane Only Support Opens Select one option above. Both options above B3 BACK SUPPORT Active Contour Back Support with TRU-Select size in Back Support Dimensions B3 BACK SUPPORT POSTIONI TRU-Balance 3 Static Back. Angle can be part of the Property of the Select System of the Property of the Select System of the Select Sy	ith Power recline or TB tions' if selected. ve include a metal active -Comfort 2 Back Cu NG oreset manually. vailable with TB3 flip-b	below. Ignore all 'Back Cane' option 33 flip-back arm supports. e contour back support shell, TRU-Comushion and Wedge Inserts.	ns. Ifort 2 back cushion, and a set of the	Standard FOG Standard Standard FOG
ACKREST SPECIFICATIONS TRU-Balance 3 Back Support System. See Back Canes Only System. Not available we Move directly to 'Back Cane Only Support Opens Select one option above. Both options above B3 BACK SUPPORT Active Contour Back Support with TRU-Select size in Back Support Dimensions B3 BACK SUPPORT POSTIONI TRU-Balance 3 Static Back. Angle can be part of the Select System of the	ith Power recline or TB tions' if selected. ve include a metal active -Comfort 2 Back Cu NG oreset manually. vailable with TB3 flip-b	below. Ignore all 'Back Cane' option 33 flip-back arm supports. e contour back support shell, TRU-Com ushion and Wedge Inserts.	ns. Ifort 2 back cushion, and a set of the	Standar FOr of wedge inser Standar Standar FOr

21"H.

24"H.

•

25″H.

BACK SUPPORT DIMENSIONS

Compatible with TB3 and Back Canes options above. Back Support can be ± -4 of seat width with TB3 Back Support System, but must be same as seat width with Back Canes Only System.

Backrest Support Width Package. –		12"-14"W.	14"-16"W.	16"-20"W.
buckiest supp	ore widen i dekage.	18"-22"W.	20"-24"W.	
Back	12″W.	14″W.	16″W.	17"W.
Support	18″W.	19″W.	20"W.	21″W.
Width.	22″W.	24″W.		
Back	14"H. <i>12"W back only</i> .	15"H. <i>12"W back only</i> .	16″H.	17″H.
Support	18″H.	19"H.	20″H.	21″H.
Height. From seat	22″H.	23″H.	24"H.	25″H.
pan.	26"H.	27″H.	28″H.	29″H.

ARM SUPPORTS

TB Flex Removable, Quick Release. Adjustment range 9" to 14" from seat pan. Minimum seat depth 15".				Standard	
Paediatric Single Post	Drop-in Removable. <i>Adjust</i>	ment range 7.75″- 9.75″ from :	seat pan. 10″ pads only.		FOC
Single Post Drop-in Re	movable. <i>Adjustment range</i>	11″-17″ from seat pan. Minim	um seat depth 14″.		FOC
2-Post Flip-up Remova	able. Adjustment range 9" to 1.	3″ from seat pan. Minimum se	eat depth 16″.		FOC
Height Adjustable, Rei	movable, Heavy Duty.				FOC
HD Removable Height Pa	HD Removable Height Package. From seat pan. 8"-12". FOC 10"-14".				
TB3 Flip-back. Adjustme	ent range 8″-16″ from seat pan.	Includes lateral in/out adjust	ment.	•	FOC
	10" Standard				Standard
	14" Standard				FOC
Arm Support Pads.	17" Standard. TB3	only. Minimum seat depth 16°			FOC
	10" Waterfall.				FOC
14"Waterfall.					FOC

CENTRE MOUNTED LEG SUPPORTS

Manually Adjustable Ce	entre Mount Foot Platform. Min	mum seat width 14".			Standard
Paediatric Adjustable C	entre Mount Foot Platform. 12"	-14″ seat widths only.			FOC
Lower Leg Extensions. From seat pan.	8"-12". Paediatric FOC centre mount only.	10"-16". Manually adjustable only.	FOC	13"-19". Manually adjustable only.	Standard
	10"W x 6"D Split Footplat	es. Paediatric centre mou	ınt only.	•••••••	FOC
Footplates.	10"W x 8"D Split Footplat	es.			FOC
	10"W x 11"D Split Footplates.			Standard	
Calf Support.	Individual Calf Pads. 6"W x	6"H. Standard	Calf Panel.	18″W x 8″H.	FOC

INDIVIDUALLY MOUNTED LEG SUPPORTS

70° Swing-Away Leg Supports. Flip-up footplates. Adj. range 12" to 15". Minimum seat width 15".	FOC
90° Paediatric Swing-Away Leg Supports. 4"W x 6"D angle & depth Adj. fooplates. Adjustment range 7" to 11".	FOC
Manual Elevating Swing-Away Leg Supports. Flip-up footplates. Adj. range 15" to 20". Min. seat width 15".	FOC

Lower Leg Extensions. 11"-13" FOC 13.5"-16.5" FOC Standard 15.5"-19.5" From seat pan.

STEALTH HEAD SUPPORTS

FOC	UniLink 8" Comfort Plus. HMO475-17M / CP08CCFPM.
Standard	UniLink 10" Comfort Plus. HMO475-17M / CP10CCFPM.
FOC	UniLink 14" Comfort Plus. HMO475-17M / CP14CCFPM.

PELVIC BELTS

Standard Auto Buckle Lap Belt, Push Button Release.

EXPANDABLE CONTROLS

Q-Logic 3e hand controls are supplied with built-in Bluetooth. O-Logic 3e Controls No nower ontions

Q-Logic se	Controls. No power options.	Staridard
Control	Hand Control. Select position in Hand Control Mounts below.	Standard
Method.	Attendant Control Hand control mounted at rear	FOC

HAND CONTROL MOUNTS

Fixed.	Fixed. Swing-away. Swings in & out with height, tension and pivot adjustment.		
Swing-away. Swings in			
Mounting Position.	Left	Right	

SPEED PROGRAM & LIGHTS PACKAGE

4 Mph Program with Lights and indicators.	Standard
6 Mph Program with Lights and indicators.	FOC
LED Front Castor and Rear Fender Lights. <i>Includes single switch button mounted to side rail.</i> Not road legal.	Standard
Omit LED Front Castor and Rear Fender Lights.	FOC

NOTES & SPECIAL REQUESTS



Quantum®

32 Wedgwood Road, Bicester, Oxon, OX26 4UL Phone: 01869 324600 Fax: 01869 323070











FOC

Standard





