





MOTABILITY ID 714914

Q6 EDGE 2.0 WITH TB3 SEAT / POWER TILT / ADI BACK

DEALERS DETAIL	S	DELIVERY DETAILS
Dealers Name		Dealers Address
Order Date		
Address		
	Postcode	Postcode
Phone	Email	Quantum Specialist
PO No	Order Ref	① Clients Weight

BASE MODEL

12 Colour Options
Height Adjustable Removable Armrests
Centre Mount Foot Platform
TB3 Seating
14" Flat Free Drive Tyres
2" x 6" Flat Free Front Castors

Standard = Standard Factory Feature FOC = Select Instead of Standard Factory Feature



2"x 6" Flat Free Rear Castors ATX Suspension System QLNES Control System 2 x 62 ah Batteries 4 Mph (6 Km/h) 4-Pole Motors Max User Weight: 21 st 6lbs. (136 kg)

DRIVE WHEELS

	·
3" x 14" Flat Free Black Tyres. With matching colour wheel accents.	Standard
3" x 14" Pneumatic Black Tyres. With matching colour wheel accents.	FOC

COLOURS

Back in Black	Standard	Red Corvet
Green Machine	FOC	Lemon Crus
Midnight Blue	FOC	Night Train
Electric Blue	FOC	Evolution C
Pretty in Pink	FOC	Military Gre
Deep Purple	FOC	Grey Street

Red Corvette FOC

Lemon Crush* FOC

Night Train* FOC

Evolution Orange* FOC

Military Green* FOC

Grey Street* FOC

Please download our free PQ-365 app to view colours and other product features in more detail.









^{*} Extended lead-time.

EAT PACK	1015 51711 11						
12"-16"W.			12″-16″[).			
14″-16″W.			14"-16"[).			
16"-20"W			16"-20"D)			
20"-22"W			20"-22"[)			
Set width at:	•••••		Set depth at	:	•••••	•••••	•••••
TEALTH SE	AT CUSHIONS	5					
No Seat Cus	shion Required						FOO
Simplicity G	i: General Use, Fluid	Resistant Stealth-Tek	Cover. 158.7 Kg weight lin	nit.			Standard
Zen SP: Skir	Protection, 4-way	Stretch, Coolcore Cove	er. 160 Kg weight limit.				FOO
TRU-Comfo	rt 2 SPP: Skin Protec	ction, Positioning, 4-wa	ay Stretch Coolcore Co	ver. <i>158.7 Kg</i> w	veight limit.		FOO
TRU-Balance		lt. 0° to 50° COG tilt. Uses	1 power option.				Standard
Powered Tilt S	Seat to Floor Height	. From seat pan.	17	- "			40.5"
	SPECIFICATIO e 3 Back Support Sy	NS	17. 2 options below. Ignore all		18.5" tions.		19.5" Standard
TRU-Balance Back Canes	e 3 Back Support Sy Only System. <i>Not av</i>	NS rstem. Select ADI Q-Back ailable with Power recline		'Back Cane' op			Standard
TRU-Balance Back Canes Move directly Select of	e 3 Back Support Sy Only System. <i>Not av</i> to 'Back Cane Only Sup ne option above. Both op	NS rstem. Select ADI Q-Back ailable with Power recline oport Options' if selected.	2 options below. Ignore all	'Back Cane' opi orts.	tions.	and a set of v	Standard FOO
TRU-Balance Back Canes Move directly Select of	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op	NS Instem. Select ADI Q-Back It is a select ADI Q-Back It is a selected. It is a selected. It is a selected a metal	2 options below. Ignore all or TB3 flip-back arm suppo active contour back support	<i>'Back Cane' op:</i> orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOO wedge insert
TRU-Balance Back Canes Move directly Select of	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op UPPORT 2. Skin protection, 4 w	NS rstem. Select ADI Q-Back ailable with Power recline oport Options' if selected. stions above include a metal	2 options below. Ignore all or TB3 flip-back arm suppo	<i>'Back Cane' op:</i> orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOO wedge insert
TRU-Balance Back Canes Move directly Select of B3 BACK SI ADI Q-Back Enter ADI Q-Ba	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op	nstem. Select ADI Q-Back ailable with Power recline oport Options' if selected. stions above include a metal ay stretch, Coolcore cover. ere.	2 options below. Ignore all or TB3 flip-back arm suppo active contour back support	<i>'Back Cane' op:</i> orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOO wedge insert
TRU-Balance Back Canes Move directly Select of B3 BACK St ADI Q-Back Enter ADI Q-Ba	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op UPPORT 2. Skin protection, 4 w ck 2 part number h	nstem. Select ADI Q-Back ailable with Power recline oport Options' if selected. stions above include a metal ay stretch, Coolcore cover. ere.	2 options below. Ignore all or TB3 flip-back arm suppo active contour back support	<i>'Back Cane' op:</i> orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOC
TRU-Balance Back Canes Move directly Select of B3 BACK St ADI Q-Back Enter ADI Q-Ba	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op UPPORT 2. Skin protection, 4 w ck 2 part number h	ns rstem. Select ADI Q-Back ailable with Power recline oport Options' if selected. vitions above include a metal ay stretch, Coolcore cover. ere. FIONING e can be preset manually.	2 options below. Ignore all or TB3 flip-back arm suppo active contour back support	<i>'Back Cane' op:</i> orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOO wedge insert Standard
TRU-Balance Back Canes Move directly Select of B3 BACK SI ADI Q-Back Enter ADI Q-Ba B3 BACK SI TRU-Balance ACK CANE	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op UPPORT 2. Skin protection, 4 w ck 2 part number h UPPORT POST e 3 Static Back. Angl	rstem. Select ADI Q-Back ailable with Power recline oport Options' if selected. bitions above include a metal ay stretch, Coolcore cover. ere. FIONING e can be preset manually.	2 options below. Ignore all or TB3 flip-back arm suppo active contour back support	'Back Cane' opi orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOC wedge insert Standard
TRU-Balance Back Canes Move directly Select of B3 BACK SI ADI Q-Back Enter ADI Q-Ba B3 BACK SI TRU-Balance ACK CANE ADI Back Su	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op UPPORT 2. Skin protection, 4 w ck 2 part number h UPPORT POST e 3 Static Back. Angl	rstem. Select ADI Q-Back ailable with Power recline oport Options' if selected. otions above include a metal ay stretch, Coolcore cover. ere. FIONING e can be preset manually. RT n, 4 way stretch, Coolcore of	2 options below. Ignore all or TB3 flip-back arm support active contour back support. Mounts directly to TB3 syst	'Back Cane' opi orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOO wedge insert Standard
TRU-Balance Back Canes Move directly Select of B3 BACK SI ADI Q-Back Enter ADI Q-Ba B3 BACK SI TRU-Balance ACK CANE ADI Back Su	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op UPPORT 2. Skin protection, 4 w ock 2 part number h UPPORT POS e 3 Static Back. Angl ONLY SUPPO Ipport. Skin protection k Support part num y	rstem. Select ADI Q-Back ailable with Power recline apport Options' if selected. ations above include a metal ay stretch, Coolcore cover. ere. FIONING e can be preset manually. RT n, 4 way stretch, Coolcore ober here. Tool Angle Ac	2 options below. Ignore all or TB3 flip-back arm support active contour back support. Mounts directly to TB3 systems are supported to the support of the su	'Back Cane' opi orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOC wedge insert Standard
TRU-Balance Back Canes Move directly Select of B3 BACK SI ADI Q-Back Enter ADI Q-Ba TRU-Balance ACK CANE ADI Back Su Enter ADI Back Back Cane Onl	e 3 Back Support Sy Only System. Not av to 'Back Cane Only Sup ne option above. Both op UPPORT 2. Skin protection, 4 w ock 2 part number h UPPORT POS e 3 Static Back. Angl ONLY SUPPO Ipport. Skin protection k Support part num y	rstem. Select ADI Q-Back ailable with Power recline oport Options' if selected. bitions above include a metal ay stretch, Coolcore cover. ere. FIONING e can be preset manually. RT n, 4 way stretch, Coolcore of the coolco	2 options below. Ignore all or TB3 flip-back arm support active contour back support. Mounts directly to TB3 systems are supported to the support of the su	'Back Cane' opi orts. shell, TRU-Comfo	tions.	and a set of v	Standard FOG wedge insert Standard Standard

ARM SUPPORTS

2-Post Flip-up Remova	2-Post Flip-up Removable. <i>Adjustment range 9" to 13" from seat pan. Minimum seat depth 16".</i> Sta				
Paediatric Single Post	Paediatric Single Post Drop-in Removable. Adjustment range 7.75"- 9.75" from seat pan. 10" pads only.				
Single Post Drop-in Re	movable. <i>Adjustment range 1</i>	1″-17″ from seat pan. M	inimum seat depth 14".	FOC	
TB3 Flip-back. Adjustme	ent range 8″-16″ from seat pan. I	Includes lateral in/out ac	ljustment.	FOC	
Arm Cupport Dade	10" Standard	Standard	10" Waterfall. Not with Std flip-up or TB Flex.	FOC	
Arm Support Pads.	14" Standard	FOC	14" Waterfall. Not with Std flip-up or TB Flex.	FOC	

CENTRE MOUNTED LEG SUPPORTS

Manually Adjustable Centre Mount Foot Platform. Minimum seat width 14".					Standard	
Paediatric Adj. Centre M	Paediatric Adj. Centre Mount Foot Platform. 12"-14" seat widths only.					FOC
Lower Leg Extensions. From seat pan.	8"-12". Paediatric centre mount only.	FOC	10″-16″.	Standard	13″-19″.	FOC
Footplates	10"W x 6"D Split Footplates. <i>Paediatric centre mount only</i> .					
1 ootpiates.	10"W x 8"D Split Fo	ootplates.	FOC	10″W x 11″D	Split Footplates.	Standard
Calf Support.	Individual Calf Pad	s. 6″W x 6″H.				Standard

INDIVIDUALLY MOUNTED LEG SUPPORTS

70° Swing-Away Leg Supports. Flip-up footplates. Adj. range 12" to 15". Minimum seat width 15".	
90° Paediatric Swing-Away Leg Supports. 4"W x 6"D angle & depth adj. fooplates. Adjustment range 7" to 11".	FOC
Manual Elevating Swing-Away Leg Supports. Flip-up footplates. Adj. range 15" to 20". Min. seat width 15".	FOC

INDIVIDUALLY MOUNTED CONFIGURABLE LEG SUPPORTS

60° to 90° Tool Adjustable S	wing-Away L	eg Supports. <i>Flip-up</i>	extruded footplates 8.	5"W x 6"D. Select lov	vers below. Minimum seat wi	dth 15". FOC
Lower Leg Extensions. From seat pan.	11″-13″	FOC	13.5″-16.5″	Standard	15.5″-19.5″	FOC

STEALTH HEAD SUPPORTS

FOC	UniLink 8" Comfort Plus. HMO475-17M / CP08CCFPM.
Standard	UniLink 10" Comfort Plus. HMO475-17M/CP10CCFPM.
FOC	UniLink 14" Comfort Plus. HMO475-17M/CP14CCFPM.

NON-EXPANDABLE CONTROLS

QLNES Controls. 2 power option ready.		Standard
Control Method.	Hand Control. Select position in Hand Control Mounts below.	Standard
Control Metriod.	Attendant Control. Hand control mounted at rear.	FOC

HAND CONTROL MOUNTS

Fixed.			Standard
Basic swing-away.			FOC
Mounting Position.	Left	Right	

SPEED PROGRAM & LIGHTS PACKAGE

2-Pole Motors & 4 Mph Program with Lights and indicators.	Standard
2-Pole Motors & 6 Mph Program with Lights and indicators.	FOC

ACCESSORIES

Prepare Chassis for Dahl Docking System. *Dahl system not included.*

NOTES & SPECIAL REQUESTS



Quantum®

32 Wedgwood Road, Bicester, Oxon, OX26 4UL Phone: 01869 324600 Fax: 01869 323070 Email: sales@quantumrehab.co.uk Web: www.quantumrehab.co.uk MOTABILITY ID 714914 - 28/02/25 V1









Δ