





MOTABILITY ID 706911

Q6 EDGE 2.0 WITH TB3 SEAT / ILEVEL / POWER TILT / POWER RECLINE / POWER FOOTBOARD

DELIVERY DETAILS DEALERS DETAILS **Dealers Address Dealers** Name Order Date Address Postcode Postcode Phone Email **Quantum Specialist** PO No Order Ref (i) Clients Weight **BASE MODEL** 12 Colour Options 2" x 6" Flat Free Rear Castors Height Adjustable Removable Armrests ATX Suspension System Q-Logic 3e Control System **Centre Mount Foot Platform** TB3 Seating 2 x 62 ah Batteries Auto Buckle Lap Belt 4 Mph (6 Km/h) 4-Pole Motors Max User Weight: 21 st 6lbs. (136 kg) 14" Flat Free Drive Tyres 2" x 6" Flat Free Front Castors Standard = Standard Factory Feature FOC = Select Instead of Standard Factory Feature

DRIVE WHEELS

3" x 14" Flat Free Black Tyres. With matching colour wheel accents.	Standard
3" x 14" Pneumatic Black Tyres. With matching colour wheel accents.	FOC

COLOURS

Back in Black	Standard	Red Corvette	FOC
Green Machine	FOC	Lemon Crush*	FOC
Midnight Blue	FOC	Night Train*	FOC
Electric Blue	FOC	Evolution Orange*	FOC
Pretty in Pink	FOC	Military Green*	FOC
Deep Purple	FOC	Grey Street*	FOC
		* Extend	led lead-time.

Please download our free PQ-365 app to view colours and other product features in more detail.





Download on the App Store



SEAT PACKAGES - SEAT WIDTH

SEAT PACKAGES - SEAT DEPTH

14″-16″W.	
16″-20″W	
20″-22″W	
Set width at:	

14"-16"D. 16"-20"D 20"-22"D

Set depth at:

Minimum seat size of 14"W x 14"D required for powered centre mount foot platform when iLevel is selected.

STEALTH SEAT CUSHIONS

-

ŧ,

No Seat Cushion Required
Simplicity G: General Use, Fluid Resistant Stealth-Tek Cover. 158.7 Kg weight limit.
Zen SP: Skin Protection, 4-way Stretch, Coolcore Cover. 160 Kg weight limit.
TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. 158.7 Kg weight limit.

Please note that seat cushions may not be available in all width and depth combinations. Refer to our Stealth Cushion Order Forms for size availability.

SEAT POSITIONING

iLevel Powered Seat Lift & Tilt. 12" lift & 50° tilt. Up to 3.5 Mph drive speed while elevated. Uses 2 power options.				
Powered iLevel Lift & Tilt Seat to Floor Height. From seat pan.	17.5″	18.5″	19.5″	

BACKREST SPECIFICATIONS

 TRU-Balance 3 Back Support System. Select TB3 back options below.
 Standard

Include a metal active contour back support shell, TRU-Comfort 2 back cushion, and a set of wedge inserts.

TB3 BACK SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. Select size in Back Support Dimensions.

TB3 BACK SUPPORT POSTIONING

TRU-Balance 3 Powered Recline. 175° with sheer reduction. Uses 1 power option. Standard

BACK SUPPORT DIMENSIONS

Back Support can be +/- 4" of seat width with TB3 Back Support System.

Backrest Support Width Package.	12″-14″W.	14"-16"W.	16″-20″W.	
backlest Support Mathin ackage.		18″-22″W.	20″-24″W.	
Back	12″W.	14″W.	16″W.	17″W.
Support	18″W.	19″W.	20″W.	21″W.
Width.	22″W.	24″W.		
Back	19″H.	20″H.	21″H.	22″H.
Support	23″H.	24″H.	25″H.	26″H.
Height. From seat	27″H.	28″H.	29″H.	30″H.
pan.	31″H.	32″H.		

Standard

ARM SUPPORTS 2-Post Flip-up Removable. Adjustment range 9" to 13" from seat pan. Minimum seat depth 16". Standard Paediatric Single Post Drop-in Removable. Adjustment range 7.75" - 9.75" from seat pan. 10" pads only. FOC Single Post Drop-in Removable. Adjustment range 11"-17" from seat pan. Minimum seat depth 14". FOC FOC TB3 Flip-back. Adjustment range 8"-16" from seat pan. Includes lateral in/out adjustment. 10″ Standard Standard 10" Waterfall. Not with Std flip-up or TB Flex. FOC Arm Support Pads. FOC 14″ Standard 14" Waterfall. Not with Std flip-up or TB Flex. FOC

CENTRE MOUNTED LEG SUPPORTS

Power Elevating Articulating Centre Mount Foot Platform. Minimum seat width 14". Uses 1 power option.				Standard
Lower Leg Extensions. From seat pan.	10″-16″.	FOC	13″-19″.	Standard
Footplates.	10″W x 8″D Split Footpl	ates.		FOC
	10″W x 11″D Split Footp	olates.		Standard
Calf Support.	Individual Calf Pads. 6"	V x 6″H.		Standard
Call Support.	Calf Panel. 18"W x 8"H.			Standard
	Certain configurations may result	in reduced ground clea	rance below footplates. Contact Quar	ntum Technical for information.

STEALTH HEAD SUPPORTS

UniLink 8" Comfort Plus. HMO475-17M / CP08CCFPM.	FOC
UniLink 10" Comfort Plus. HMO475-17M / CP10CCFPM.	FOC
UniLink 14" Comfort Plus. HMO475-17M / CP14CCFPM.	FOC

Please visit stealthproducts.com for alternative head supports.

EXPANDABLE CONTROLS

Q-Logic 3e Controls	5. 5 power option ready.			Standard
iAccess OLED 4 Button Mounted to opposite armr Supplied FOC when ilevel i	est unless specified.	FOC	Push Button iAccess Toggle Lever iAccess	If iAccess is selected choose either Push Button or Toggle leaver option.
Hand Control. Select position in Hand Control Mounts below.			Standard	
Control Method.	Attendant Con	trol. Hand control	mounted at rear.	FOC
******		•••••	• • • • • • • • • • • • • • • • • • • •	

Q-Logic 3e hand controls are supplied with built-in Bluetooth.

HAND CONTROL MOUNTS

Fixed.		Stand	dard
Basic swing-away.			FOC
Mounting Position.	Left	Right	

SPEED PROGRAM & LIGHTS PACKAGE

2-Pole Motors & 4 Mph Program with Lights and indicators.

2-Pole Motors & 6 Mph Program with Lights and indicators.

ACCESSORIES

Prepare Chassis for Dahl Docking System. Dahl system not included.

NOTES & SPECIAL REQUESTS



Quantum® 32 Wedgwood Road, Bicester, Oxon, OX26 4UL Phone: 01869 324600 Fax: 01869 323070 Email: sales@quantumrehab.co.uk Web: www.quantumrehab.co.uk MOTABILITY ID 706911 - 19/02/25 V1







4

FOC

Standard FOC