

EDGE 3 STRETTO WITH TB3 SEATING

DEALERS DETAILS

Dealers Name	
Order Date	
Address	
Postcode	
Phone	Email
PO No	Order Ref

DELIVERY DETAILS

Dealers Address	
Postcode	
Quantum Specialist	
Ⓢ Clients Weight (required for suspension settings)	

BASE MODEL

14 Colour Options
Height Adj. Removable Arm Supports
Centre Mount Foot Platform
TB3 Seating
12.5" Flat Free Drive Tyres
2" x 5" Flat Free Front Castors
2" x 6" Flat Free Rear Castors



SRS Suspension System
QLNES Control System
2 x 62 ah Batteries
4 Mph (6 Km/h) Motors
Max User Weight:
21 st 6lbs. (136 kg)

Standard = Standard Factory Feature
FOC = Select Instead of Standard Factory Feature

DRIVE WHEELS

3" x 12.5" Flat Free Black Tyres.	Standard
3" x 12.5" Pneumatic Black Tyres.	FOC
3" x 14" Flat Free Black Tyres. <i>With matching colour wheel accents.</i>	FOC
3" x 14" Pneumatic Black Tyres. <i>With matching colour wheel accents.</i>	FOC

COLOURS

Back in Black	Standard	Pretty in Pink	FOC
Green Machine	FOC	Lemon Crush*	FOC
Midnight Blue	FOC	Night Train*	FOC
Electric Blue	FOC	Evolution Orange*	FOC
Blue Jean	FOC	Military Green*	FOC
Deep Purple	FOC	Grey Street*	FOC
Red Corvette	FOC	Raspberry Beret*	FOC

* Extended lead-time.

Please download our free PQ-365 app to view colours and other product features in more detail.



SEAT PACKAGES - SEAT WIDTH

12"-16"W
14"-16"W
16"-20"W
Set width at:

SEAT PACKAGES - SEAT DEPTH

12"-16"D
14"-16"D
16"-20"D
Set depth at:

STEALTH SEAT CUSHIONS

No Seat Cushion Required	FOC
Simplicity G: General Use, Fluid Resistant Stealth-Tek Cover. <i>158.7 Kg weight limit.</i>	Standard
Zen SP: Skin Protection, 4-way Stretch, Coolcore Cover. <i>160 Kg weight limit.</i>	FOC
TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. <i>158.7 Kg weight limit.</i>	FOC

Please note that seat cushions may not be available in all width and depth combinations. Refer to our Stealth Cushion Order Forms for size availability.

SEAT POSITIONING

Static Seat.	Standard
Static Seat to Floor Height. <i>From seat pan.</i>	16" 17" 18"

BACKREST SPECIFICATIONS

TRU-Balance 3 Back Support System. <i>Select TB3 back options below. Ignore all 'Back Cane' options.</i>	Standard
Back Canes Only System. <i>Not available with TB3 flip-back arm supports. Move directly to 'Back Cane Only Support Options' if selected.</i>	FOC

Select one option above. Both options above include a metal active contour back support shell, TRU-Comfort 2 back cushion, and a pair of plastic lateral wedge inserts.

TB3 BACK SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Lateral Wedges. <i>Select size in Back Support Dimensions</i>	Standard
---	----------

TB3 BACK SUPPORT POSTIONING

TRU-Balance 3 Static Back. <i>Angle can be preset manually.</i>	Standard
TRU-Balance 3 Flip-forward Back. <i>Not available with TB3 flip-back arm supports. Not suitable for occupied transport.</i>	FOC

BACK CANE ONLY SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Lateral Wedges. <i>Select size in Back Support Dimensions</i>						Standard
Back Cane Only Support Positioning.	Tool Angle Adjustable. <i>85° to 120° in 5° increments.</i>					Standard
	Flip-forward Back Canes. <i>Not suitable for occupied transport.</i>					FOC
Back Cane Height. <i>From seat pan.</i>	16"H	17 "H	18 "H	19 "H	20 "H	
	21 "H	22 "H	23 "H	24 "H	25 "H	

BACK SUPPORT DIMENSIONS

Compatible with TB3 and Back Canes options above. Ignore Back Support Dimensions if omit back support is selected in TB3 or Back Canes sections. Back Support can be +/- 4" of seat width with TB3 Back Support System, but must be same as seat width with Back Canes Only System unless -2" or -4" Endo Mounts have been selected.

Backrest Support Width Package.		12"-14"W	14"-16"W	16"-20"W
		18"-22"W	20"-24"W	
Back Support Width.	12"W	14"W	16"W	17"W
	18 "W	19"W	20"W	21"W
	22"W	24"W		
Back Support Height. <i>From seat pan.</i>	14"H. <i>12"W back only.</i>	15"H. <i>12"W back only.</i>	16"H.	17"H.
	18"H.	19"H.	20"H.	21"H.
	22"H.	23"H.	24"H.	25"H. <i>Not available with 24"W back.</i>
	26"H. <i>Not available with 24"W back.</i>	27"H. <i>Not available with 24"W back.</i>	28"H. <i>Not available with 24"W back.</i>	29"H. <i>Not available with 24"W back.</i>

ARM SUPPORTS

2-Post Flip-up Removable. <i>Adjustment range 9" to 13" from seat pan. Minimum seat depth 16".</i>			Standard	
Single Post Drop-in Removable. <i>Adjustment range 11"-17" from seat pan. Minimum seat depth 14".</i>			FOC	
Paediatric Single Post Drop-in Removable. <i>Adjustment range 7.75"- 9.75" from seat pan. 10" pads only.</i>			FOC	
TB3 Flip-back. <i>Adjustment range 8"-16" from seat pan. Includes lateral in/out adjustment.</i>			FOC	
Arm Support Pads	10" Standard	Standard	10" Waterfall. <i>Not with TB3 Flip-back.</i>	FOC
	14" Standard	FOC	14" Waterfall. <i>Not with TB3 Flip-back.</i>	FOC
	17" Standard. <i>TB3 only. Minimum seat depth 16"</i>	FOC		

CENTRE MOUNTED LEG SUPPORTS

Manually Adjustable Centre Mount Foot Platform. <i>Minimum seat width 14"</i>				Standard
Paediatric Adj. Centre Mount Foot Platform. <i>12"-14" seat widths only.</i>				FOC
Lower Leg Extensions. <i>From seat pan.</i>	8"-12". <i>Paediatric centre mount only.</i>	FOC	10"-16". <i>Manually adjustable.</i>	Standard
Foot Supports.	10"W x 6"D Split Foot Supports. <i>Paediatric centre mount only.</i>	FOC	10"W x 8"D Split Foot Supports.	FOC
	10"W x 11"D Split Foot Supports.			Standard
Calf Support.	Individual Calf Pads. <i>6"W x 6"H.</i>			Standard

INDIVIDUALLY MOUNTED LEG SUPPORTS

70° Swing-away. <i>Flip-up footplates. Adj. range 12" to 15". Minimum seat width 15".</i>	FOC
Manual Elevating Swing-Away. <i>Flip-up footplates. Adj. range 15" to 20". Min. seat width 15".</i>	FOC

INDIVIDUALLY MOUNTED CONFIGURABLE LEG SUPPORTS

60° to 90° Tool Adjustable Swing-away. <i>Angle & depth adjustable footplates 6"W x 8"D. Select lowers below. Minimum seat width 15".</i>						FOC
60° to 90° Lower Leg Extensions. <i>From seat pan.</i>	11"-13"	FOC	13.5"-16.5"	Standard	15.5"-19.5"	FOC

Adjustment ranges above are from seat pan to foot supports. Individual leg supports supplied with heel loops. Elevating leg supports supplied with calf supports.

STEALTH HEAD SUPPORTS

UniLink 10" Comfort Plus. <i>HMO475-17M / CP10CCFPM.</i>	Standard
UniLink 14" Comfort Plus. <i>HMO475-17M / CP14CCFPM.</i>	FOC

PELVIC BELTS

Auto Buckle Lap Belt, Push Button Release.	Standard
--	----------

EXPANDABLE CONTROLS

QLNES.		Standard
Control Method.	Hand Control. <i>Select position in Hand Control Mounts below.</i>	Standard
	Attendant Control. <i>Hand control mounted at rear.</i>	FOC

Please visit stealthproducts.com for alternative control options such as mini joysticks, head arrays & switches.

HAND CONTROL MOUNTS

Fixed.				Standard	
Basic Swing-away.				FOC	
●●●	Mounting Position.	Left	FOC	Right	Standard

SPEED PROGRAM & LIGHTS PACKAGE

4 Mph Program with Lights and indicators.	Standard
6 Mph Program with Lights and indicators.	FOC
LED Fender Lights. <i>Includes single switch button mounted to side rail. Not road legal.</i>	Standard
Omit LED Fender Lights.	FOC

NOTES & SPECIAL REQUESTS



Quantum®
 32 Wedgwood Road, Bicester,
 Oxon, OX26 4UL
 Phone: 01869 324600
 Fax: 01869 323070
 Email: sales@quantumrehab.co.uk
 Web: www.quantumrehab.co.uk
Motability ID 707384 - 01/04/25 V1

