

MOTABILITY ID 721038

## Q6 EDGE 2.0 WITH TB3 SEAT

### DEALERS DETAILS

Dealers Name \_\_\_\_\_

Order Date \_\_\_\_\_

Address \_\_\_\_\_

Postcode \_\_\_\_\_

Phone \_\_\_\_\_ Email \_\_\_\_\_

PO No \_\_\_\_\_ Order Ref \_\_\_\_\_

### DELIVERY DETAILS

Dealers Address \_\_\_\_\_

Postcode \_\_\_\_\_

Quantum Specialist \_\_\_\_\_

Ⓢ Clients Weight \_\_\_\_\_

### BASE MODEL

- 12 Colour Options
- Height Adj. Removable Arm Supports
- Centre Mount Foot Platform
- TB3 Seating
- Auto Buckle Lap Belt
- 14" Flat Free Drive Tyres
- 2" x 6" Flat Free Front Castors



- 2" x 6" Flat Free Rear Castors
- ATX Suspension System
- QLNES Control System
- 2 x 62 ah Batteries
- 4 Mph (6 Km/h) 4-Pole Motors
- Max User Weight: 21 st 6lbs. (136 kg)

Standard = Standard Factory Feature  
 FOC = Select Instead of Standard Factory Feature

### DRIVE WHEELS

3" x 14" Flat Free Black Tyres. <i>With matching colour wheel accents.</i>	Standard
3" x 14" Pneumatic Black Tyres. <i>With matching colour wheel accents.</i>	FOC

### COLOURS

Back in Black	Standard	Red Corvette	FOC
Green Machine	FOC	Lemon Crush*	FOC
Midnight Blue	FOC	Night Train*	FOC
Electric Blue	FOC	Evolution Orange*	FOC
Pretty in Pink	FOC	Military Green*	FOC
Deep Purple	FOC	Grey Street*	FOC

\* Extended lead-time.

Please download our free PQ-365 app to view colours and other product features in more detail.



## SEAT PACKAGES - SEAT WIDTH

12"-16"W.
14"-16"W.
16"-20"W
20"-22"W
Set width at:

## SEAT PACKAGES - SEAT DEPTH

12"-16"D.
14"-16"D.
16"-20"D
20"-22"D
Set depth at:

## STEALTH SEAT CUSHIONS

No Seat Cushion Required	FOC
Simplicity G: General Use, Fluid Resistant Stealth-Tek Cover. <i>158.7 Kg weight limit.</i>	Standard
Zen SP: Skin Protection, 4-way Stretch, Coolcore Cover. <i>160 Kg weight limit.</i>	FOC
TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. <i>158.7 Kg weight limit.</i>	FOC

Please note that seat cushions may not be available in all width and depth combinations. Refer to our Stealth Cushion Order Forms for size availability.

## SEAT POSITIONING

Static Seat.	Standard
Static Seat to Floor Height. <i>From seat pan.</i>	16.5"      17.5"      18.5"

## BACKREST SPECIFICATIONS

TRU-Balance 3 Back Support System. <i>Select TB3 back options below. Ignore all 'Back Cane' options.</i>	Standard
Back Canes Only System. <i>Not available with TB3 flip-back arm supports. Move directly to 'Back Cane Only Support Options' if selected.</i>	FOC

Select one option above. Both options above include a metal active contour back support shell, TRU-Comfort 2 back cushion, and a set of wedge inserts.

## TB3 BACK SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. <i>Select size in Back Support Dimensions</i>	Standard
--	----------

## TB3 BACK SUPPORT POSTIONING

TRU-Balance 3 Static Back. <i>Angle can be preset manually.</i>	Standard
TRU-Balance 3 Flip-forward Back. <i>Not available with TB3 flip-back arm supports or powered recline. Not suitable for occupied transport.</i>	FOC

## BACK CANE ONLY SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. <i>Select size in Back Support Dimensions.</i>	Standard
Back Cane Only Support Positioning. Tool Angle Adjustable. <i>85° to 120° in 5° increments.</i>	Standard
Back Cane Height. <i>From seat pan.</i>	16"H.      17"H.      18"H.      19"H.      20"H. 21"H.      22"H.      23"H.      24"H.      25"H.

## BACK SUPPORT DIMENSIONS

Compatible with TB3 and Back Canes options above. Ignore Back Support Dimensions if omit back support is selected in TB3 or Back Canes sections. Back Support can be +/- 4" of seat width with TB3 Back Support System, but must be same as seat width with Back Canes Only System unless -2" or -4" Endo Mounts have been selected.

Backrest Support Width Package.		12"-14"W.	14"-16"W.	16"-20"W.
		18"-22"W.	20"-24"W.	
Back Support Width.	12"W.	14"W.	16"W.	17"W.
	18"W.	19"W.	20"W.	21"W.
	22"W.	24"W.		
Back Support Height. <i>From seat pan.</i>	14"H. <i>12"W back only.</i>	15"H. <i>12"W back only.</i>	16"H.	17"H.
	18"H.	19"H.	20"H.	21"H.
	22"H.	23"H.	24"H.	25"H. <i>Not available with 24"W back.</i>
	26"H. <i>Not available with 24"W back.</i>	27"H. <i>Not available with 24"W back.</i>	28"H. <i>Not available with 24"W back.</i>	29"H. <i>Not available with 24"W back.</i>

## ARM SUPPORTS

2-Post Flip-up Removable. <i>Adjustment range 9" to 13" from seat pan. Minimum seat depth 16"</i>	Standard	
Paediatric Single Post Drop-in Removable. <i>Adjustment range 7.75"- 9.75" from seat pan. 10" pads only.</i>	FOC	
Single Post Drop-in Removable. <i>Adjustment range 11"-17" from seat pan. Minimum seat depth 14"</i>	FOC	
TB3 Flip-back. <i>Adjustment range 8"-16" from seat pan. Includes lateral in/out adjustment.</i>	FOC	
Arm Support Pads.	10" Standard Standard 10" Waterfall. <i>Not with TB3 Flip-back</i>	FOC
	14" Standard FOC 14" Waterfall. <i>Not with TB3 Flip-back</i>	FOC

## CENTRE MOUNTED LEG SUPPORTS

Base Mounted Flip-up Foot Platform. <i>Mounted to chassis.</i>	FOC	
Paediatric Adj. Centre Mount Foot Platform. <i>12"-14" seat widths only.</i>	FOC	
Manually Adjustable Centre Mount Foot Platform. <i>Minimum seat width 14"</i>	Standard	
Lower Leg Extensions. <i>From seat pan.</i>	8"-12". <i>Paediatric centre mount only.</i> FOC 10"-16". Standard 13"-19". FOC	
Foot Supports.	10"W x 6"D Split Foot Supports. <i>Paediatric centre mount only.</i>	FOC
	10"W x 8"D Split Foot Supports. FOC 10"W x 11"D Split Foot Supports. Standard	Standard
Calf Support.	Individual Calf Pads. <i>6"W x 6"H.</i>	Standard

## INDIVIDUALLY MOUNTED LEG SUPPORTS

70° Swing-Away. <i>Flip-up footplates. Adj. range 12" to 15". Minimum seat width 15"</i>	FOC
Manual Elevating Swing-Away. <i>Flip-up footplates. Adj. range 15" to 20". Min. seat width 15"</i>	FOC

## INDIVIDUALLY MOUNTED CONFIGURABLE LEG SUPPORTS

60° to 90° Tool Adjustable Swing-Away. <i>Angle &amp; depth adjustable footplates 6"W x 8"D. Select lowers below. Minimum seat width 15"</i>	FOC
Lower Leg Extensions. <i>From seat pan.</i>	11"-13" FOC 13.5"-16.5" Standard 15.5"-19.5" FOC

Certain configurations may result in reduced ground clearance below footplates. Contact Quantum Technical for information. Adjustment ranges above are from seat pan to footplates. Individual legrests are supplied with heel loops.

## STEALTH HEAD SUPPORTS

UniLink 8" Comfort Plus. <i>HMO475-17M / CP08CCFPM.</i>	FOC
UniLink 10" Comfort Plus. <i>HMO475-17M / CP10CCFPM.</i>	Standard
UniLink 14" Comfort Plus. <i>HMO475-17M / CP14CCFPM.</i>	FOC

Please visit [stealthproducts.com](http://stealthproducts.com) for alternative head supports.

## NON-EXPANDABLE CONTROLS

QLNES Controls. <i>With no power options.</i>	Standard
Control Method. Hand Control. <i>Select position in Hand Control Mounts below.</i>	Standard
Attendant Control. <i>Hand control mounted at rear.</i>	FOC

## HAND CONTROL MOUNTS

Fixed.	Standard
Basic swing-away.	FOC
Mounting Position. Left Right	

## SPEED PROGRAM & LIGHTS PACKAGE

2-Pole Motors & 4 Mph Program with Lights and indicators.	Standard
2-Pole Motors & 6 Mph Program with Lights and indicators.	FOC

## ACCESSORIES

Prepare Chassis for Dahl Docking System. <i>Dahl system not included.</i>	FOC
---	-----

## NOTES & SPECIAL REQUESTS



**Quantum®**  
 32 Wedgwood Road, Bicester,  
 Oxon, OX26 4UL  
 Phone: 01869 324600  
 Fax: 01869 323070  
 Email: [sales@quantumrehab.co.uk](mailto:sales@quantumrehab.co.uk)  
 Web: [www.quantumrehab.co.uk](http://www.quantumrehab.co.uk)  
**MOTABILITY ID 721038 - 01/04/25 V1**

