





MOTABILITY ID 721032

Q6 EDGE 2.0 WITH TB3 SEAT / POWER TILT

DEALERS DETAILS		
Dealers Name		
Order Date		
Address		
	Postcode	
Phone	Email	
PO No	Order Ref	

DELIVERY DETAILS

Dealers Address

Quantum Specialist

⁽ⁱ⁾ Clients Weight

BASE MODEL

12 Colour Options Height Adj. Removable Arm Supports Centre Mount Foot Platform TB3 Seating Auto Buckle Lap Belt 14" Flat Free Drive Tyres 2" x 6" Flat Free Front Castors



2" x 6" Flat Free Rear Castors ATX Suspension System QLNES Control System 2 x 62 ah Batteries 4 Mph (6 Km/h) 4-Pole Motors Max User Weight: 21 st 6lbs. (136 kg)

Postcode

Standard = Standard Factory Feature FOC = Select Instead of Standard Factory Feature

DRIVE WHEELS

3" x 14" Flat Free Black Tyres. With matching colour wheel accents.	Standard
3" x 14" Pneumatic Black Tyres. With matching colour wheel accents.	FOC

COLOURS

Back in Black	Standard	Red Corvette	
Green Machine	FOC	Lemon Crush*	FOC
Midnight Blue	FOC	Night Train*	FOC
Electric Blue	FOC	Evolution Orange*	
Pretty in Pink	FOC	Military Green*	FOC
Deep Purple	FOC	Grey Street*	FOC
		* Extended lead-	

Please download our free PQ-365 app to view colours and other product features in more detail.





Download on the App Store



SEAT PACKAGES - SEAT WIDTH

12″-16″W.	12″-16″D.
14″-16″W.	14"-16"D.
16″-20″W	16″-20″D
20″-22″W	20"-22"D
Set width at:	Set depth at:

STEALTH SEAT CUSHIONS

No Seat Cushion Required	FOC
Simplicity G: General Use, Fluid Resistant Stealth-Tek Cover. 158.7 Kg weight limit.	Standard
Zen SP: Skin Protection, 4-way Stretch, Coolcore Cover. 160 Kg weight limit.	FOC
TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. 158.7 Kg weight limit.	FOC
IRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. 158.7 Kg weight limit. Please note that seat cushions may not be available in all width and depth combinations. Refer to our Stealth Cushion Order For	ms for size a

SEAT PACKAGES - SEAT DEPTH

SEAT POSITIONING

TRU-Balance 3 Powered Seat Tilt. 0° to 50° COG tilt. Uses 1 power opt	ion.		Standard
Powered Tilt Seat to Floor Height. From seat pan.	17.5″	18.5″	19.5″

BACKREST SPECIFICATIONS

TRU-Balance 3 Back Support System. Select TB3 back options below. Ignore all 'Back Cane' options.	Standard
Back Canes Only System. Not available with TB3 flip-back arm supports. Move directly to 'Back Cane Only Support Options' if selected.	FOC

Select one option above. Both options above include a metal active contour back support shell, TRU-Comfort 2 back cushion, and a set of wedge inserts.

TB3 BACK SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts.StandardSelect size in Back Support DimensionsStandard

TB3 BACK SUPPORT POSTIONING

TRU-Balance 3 Static Back. Angle can be preset manually.	Standard
TRU-Balance 3 Flip-forward Back. Not available with TB3 flip-back arm supports or powered recline. Not suitable for occupied transport.	FOC

BACK CANE ONLY SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. Select size in Back Support Dimensions.				port Dimensions. Standard	
Back Cane OnlyTool Angle Adjustable. 85° to 120° in 5° increments.Support Positioning.				Standard	
Back Cane	16″H.	17″H.	18″H.	19″H.	20″H.
Height. From seat pan.	21″H.	22″H.	23″H.	24″H.	25″H.

BACK SUPPORT DIMENSIONS

Backrest Support Width Package.		12″-14″W.	14″-16″W.	16"-20"W.
backiest supp	ort mattri ackage.	18"-22"W.	20″-24″W.	
Back	12″W.	14″W.	16″W.	17″W.
Support	18″W.	19″W.	20″W.	21″W.
Width. 22"W.		24″W.		
	14"H. 12"W back only.	15"H. 12"W back only.	16″H.	17″H.
Back Support	18″H.	19″H.	20″H.	21″H.
Height. From seat	22″H.	23″H.	24″H.	25"H. Not available with 24"W back.
pan.	26"H. Not available with 24"W back.	27"H. Not available with 24"W back.	28"H. Not available with 24"W back.	29"H. Not available with 24"W back.

Compatible with TB3 and Back Canes options above. Ignore Back Support Dimensions if omit back support is selected in TB3 or Back Canes sections. Back Support can be +/- 4" of seat width with TB3 Back Support System, but must be same as seat width with Back Canes Only System unless -2" or -4" Endo Mounts have been selected.

ARM SUPPORTS

		Standard	
- Paediatric Single Post Drop-in Removable. <i>Adjustment range</i> 7.75″- 9.75″ from seat pan. 10″ pads only.			
Single Post Drop-in Removable. Adjustment range 11"-17" from seat pan. Minimum s	nt depth 14".	FOC	
TB3 Flip-back. Adjustment range 8"-16" from seat pan. Includes lateral in/out adjustment.			
	Waterfall. Not with TB3 Flip-back	FOC	
Arm Support Pads 14" Standard FOC 14	Waterfall. Not with TB3 Flip-back	FOC	

CENTRE MOUNTED LEG SUPPORTS

Manually Adjustable Ce	ntre Mount Foot Platfor	m. Minimum se	eat width 14″.			Standard
Paediatric Adjustable Ce	entre Mount Foot Platfo	rm. 12"-14" sea	t widths only.			FOC
Lower Leg Extensions. From seat pan.	8"-12". Paediatric centre mount only.	FOC	10″-16″.	Standard	13"-19".	FOC
Foot Supports.	10"W x 6"D Split Fo	oot Supports.	Paediatric centr	re mount only.		FOC
	10″W x 8″D Split Fo	oot Supports.	FOC	10″W x 11″D	Split Foot Supports.	Standard
Calf Support.	Individual Calf Pad	s. 6″W x 6″H.				Standard

INDIVIDUALLY MOUNTED LEG SUPPORTS

70° Swing-Away. Flip-up footplates. Adj. range 12" to 15". Minimum seat width 15".	FOC
Manual Elevating Swing-Away. Flip-up footplates. Adj. range 15" to 20". Min. seat width 15".	FOC

INDIVIDUALLY MOUNTED CONFIGURABLE LEG SUPPORTS

	60° to 90° Tool Adjustal	Ainimum seat width 15"	FOC				
	Lower Leg Extensions. From seat pan.	11″-13″	FOC	13.5″-16.5″	Standard	15.5"-19.5"	FOC
•		5		5		ntact Quantum Technical for eg supports are supplied wit	

STEALTH HEAD SUPPORTS

UniLink 8" Comfort Plus. HMO475-17M / CP08CCFPM.

UniLink 10" Comfort Plus. HMO475-17M / CP10CCFPM.

UniLink 14" Comfort Plus. HMO475-17M / CP14CCFPM.

Please visit stealthproducts.com for alternative head supports.

FOC

FOC

Standard

Standard

FOC

FOC

NON-EXPANDABLE CONTROLS

QLNES Controls. 2 por	Standard	
Control Method. –	Hand Control. Select position in Hand Control Mounts below.	Standard
control method. –	Attendant Control. Hand control mounted at rear.	FOC

HAND CONTROL MOUNTS

Fixed.			Standard
Basic swing-away.			FOC
Mounting Position.	Left	Right	

SPEED PROGRAM & LIGHTS PACKAGE

2-Pole Motors & 4 Mph Program with Lights and indicators.

2-Pole Motors & 6 Mph Program with Lights and indicators.

ACCESSORIES

Prepare Chassis for Dahl Docking System. Dahl system not included.

NOTES & SPECIAL REQUESTS



Quantum® 32 Wedgwood Road, Bicester, Oxon, OX26 4UL Phone: 01869 324600 Fax: 01869 323070 Email: sales@quantumrehab.co.uk Web: www.quantumrehab.co.uk MOTABILITY ID 721032 - 01/04/25 V1



